

THE TECHNICAL CONTENT OF THIS DOCUMENT IS APPROVED UNDER
THE AUTHORITY OF EASA.21J.140 (C644 Iss. 1)

7.48 NANO BASKET

7.48.1 GENERAL

This supplement shall be inserted in the Maintenance Manual, in Section 7: 'Supplements' with the revisions record sheet amended accordingly.

Information contained herein supplements, or in the case of conflict, supersedes that contained in the basic Maintenance Manual. For Limitations, Procedures, and Performance Data not contained in this supplement, consult the basic Hot Air Balloon Maintenance Manual.

7.48.2 ENVELOPE REPAIRS

No change.

7.48.3 BASKET REPAIRS

7.48.3.1 ROUTINE MAINTENANCE

All fasteners should be visually inspected before every flight for damage, wear or distortion. Ensure that all the retaining screws are tight.

7.48.4 FUEL SYSTEM REPAIRS

No change.

7.48.5 INSTRUMENT REPAIRS

No change.

Basket Type:			
Part No.:		Serial No.:	

7.48.6 MAINTENANCE SCHEDULE

7.48.6.5.8 Basket (additional)

Component	Check / Inspect / Record	Pass/Fail (✓)/(x)
Eye-Bolts	Check Eye-Bolts for damage, wear or distortion. Check that fasteners are tight.	
Maillon Links	Check the Maillon Links securing the basket suspension wires for damage, wear or distortion.	
Trim	Check condition / present	

7.48.6.6.5 Baskets (additional)

Basket Suspension system: The Nano basket is unique in the respect that the load path includes fasteners (eye-bolts, maillon links) rather than a continuous wires. It is essential that the retaining nuts of the eye-bolts and other components in the load path are checked for security and damage at the annual 100hr/Annual inspection.

Workpack No.	CN	Inspection Date	Inspectors Signature/No.
--------------	----	-----------------	--------------------------