MAINTENANCE SE MANUAL

Section 6: Maintenance Schedule



6.5 INSPECTION SCHEDULE

Envelope Hours at inspection date:	
Envelope hours at end of preceding cal-	
ender year	
Applicable AD or SB:	
Maintenance Programme Ref:	
Document Check:	

6.5.1 Envelope Structure

C	conent Check / Inspect / Record				Pass/Fail	
Component		Cr	neck / inspect / Reco	ra	(√)/(x)	
Crown Line	Inspect condition					
Crown Ring	Inspe	ct for damage a	nd Corrosion			
	Inspe	ect turnbacks at o	crown ring			
		ct joints betwee arachute or rip p	n vertical tapes and a panel	iny tapes overlying		
Vertical	Inspe enve	-	n vertical tapes and t	he top edge of the		
Load Tapes	Inspe	ct tapes				
	Inspe	Inspect joints between load tapes and flying cables				
	Inspect load tape protectors					
	Inspe					
Horizontal Load Tapes	Inspect horizontal load tapes					
	Inspect base tape					
Fabric	Inspe	ct for damage, p	porosity, overheating o	or weakness		
Panels	Inspe	ct joints and stit	cching			
Flying Cables	Inspect for damage, annealing, maillon links for security (if fitted)					
Grab Test	Check and Record, All colours tested (Repeat each annual inspection >250hr or at inspectors discretion). Minimum Strength= 30lb (13.6kg). Refer to Section 6.7					
Workpack No	o. CN Inspection Date Inspectors Signature/No.				No.	

19 October 2017 Amendment 4 Page 6-3



Section 6 : Maintenance Schedule

6.5.2 Deflation System

Component	Check / Inspect / Record	Pass/Fail (√)/(x)
Fabric	Inspect for damage, porosity, overheating or weakness (especially edges)	
Panels	Inspect joints and stitching	
Sewn Loops	Inspect for damage, wear, security (both on the deflation panel and envelope)	
Centralising Lines	Inspect for damage wear, security of knots	
Shroud Lines	Inspect for damage wear, security of knots	
Top strings	Inspect for damage wear, security of knots	
Control Lines	Inspect for damage wear, security of knots	
Control Line Attachments	Inspect for damage, wear, security (both on the deflation panel and envelope)	
Control Line Pulleys	Inspect for wear, free running, contamination, security of attachment	
Maillon Links	Inspect for Security, damage, heatshrink complete and undamaged	
RDS/Q-Vent Pulleys	Inspect for wear, free running, contamination, security of attachment	
Transparent	Inspect the window material for tears or cracking	
Panels	Inspect the adhesive tape fitted to the edge of the window	
Guide Rings	Inspect for damage, wear, security of attachment	
Riplocks/ Capewells	Inspect Riplocks/Capewells and check installation/function	
Arming Shackle	Inspect the condition of the quick release shackle and check that it operates smoothly (Lock Top only)	
Grab Test	Check and Record, All colours tested (Repeat each annual inspection >250hr or at inspectors discretion). Minimum Strength= 30lb (13.6kg). Refer to Section 6.7	
Parachute Edge grab Test	Cameron /T&C Envelopes only (Refer to 6.Check and Record, All colours tested (>250hr or at inspectors discretion) between the edge of the panel and the Velcro tabs. Minimum Strength= 21lb (9.5Kg)	

Workpack No.	CN	Inspection Date	Inspectors Signature/No.

Page 6-4 Amendment 4 19 October 2017

Section 6: Maintenance Schedule



6.5.3 Turning Vents/Side Dump

Component	Check / Inspect / Record	Pass/Fail (√)/(x)
Fabric	Inspect for damage, porosity, overheating or weakness (especially inside the envelope)	
Panels	Inspect joints and stitching	
Free Tapes	Inspect condition of stitching at ends of tapes	
Pulling Triangles	Inspect condition of stitching	
Control Lines	Inspect for damage wear, security of knots	
Control Line Attachments	Inspect for damage, wear, security (both on the deflation panel and envelope	
Control Line Pulleys	Inspect for wear, free running, contamination, security of attachments	
Shock Cord	Inspect condition, check operation	
Vent Line Stop	Inspect condition, correctly fitted.	

6.5.4 Envelope Temperature Measurement

Component	Check / Inspect / Record	Pass/Fail (√)/(x)
Temperature Flag	Check temperature streamer and melting link are securely attached	
Tempilabel	Inspect the Tempilabel. Record the Max. Temperature indicated in the logbook. If ≥ 121C Perform overheat inspection	

6.5.5 Test Inflation (if required)

A test inflation, as described in 6.9.4 Test Inflation After Repair, is required for Special Shape Balloons but optional for conventionally shaped balloons.

System	Check / Inspect / Record	Pass/Fail (√)/(x)
Deflation System	Inspect Seals, Functional Check	
Turning Vents	Inspect Seals, Functional Check	
Dumps	Inspect Seals, Functional Check	

Workpack No.	CN	Inspection Date	Inspectors Signature/No.

19 October 2017 Amendment 4 Page 6-5



Section 6: Maintenance Schedule

6.5.6 Grab Test Results

6.5.6.1 Grab Test Results-Envelope

Colour	Result	Colour	Result

6.5.6.2 Grab Test Results-Deflation System

Colour	Result (panel/edge)	Colour	Result (panel/edge)

Notes:

Workpack No.	CN	Inspection Date	Inspectors Signature/No.

MAINTENANCE MANUAL

Section 6: Maintenance Schedule



6.5.7 Burne	er Syste	em				
Burner T	ype:				Part No.:	
Burner Serial No.:		:			Frame Part No:	
Serialised	Parts	1		2	3	4
Coil						
Block	K					
Component		CI	neck	/ Inspect / Reco	rd	Pass/Fail (√)/(x)
	Inspect	welds for cracking	3			
	Inspect	tubes for distortion	n/de	formation/cuts/goug	es	
Burner Frame	Inspect	frame for security	of fa	asteners (heat shields	,flexi corners)	
	Inspect	frame lugs for we	ar, cr	acking.		
	Inspect	general condition	(corr	osion, heatshields)		
Gimballing	Check s	tiffness, security o	of fitt	ings		
Height adjustment	Check F	Check Function, Leaks. Check SB19				
Karabiners	Inspect	Inspect for wear, corrosion, correct function, correct type				
Burner System	Leak Ch	neck (including ma	nifolo	ds)		
Hoses	Inspect	all Hoses, check d	ates	(if applicable)		
Pressure Gauges	Check F	Pressure Gauge rea	ds ze	ro when no pressure	applied, lens present	
Pilot Valves	Check S	hut off, free move	ement	t, Correct Function, l	ubricate if necessary	
Whisper Valves	Check S	Check Shut off, free movement, Correct Function, lubricate if necessary				
Main Valves	Check S	Check Shut off, free movement, Correct Function, lubricate if necessary				
Crossflow Valve	Check Shut-off, correct operation, leakage					
Jets	Check Security of Jets, Tighten or Replace as necessary					
Coils	Check for damage, distortion, security of fasteners					
Fuel Manifolds	Check Correct Type, Inspect condition, check dates (if applicable)					
Jetstream	Jetstream Burner Mod 650 stem fitted or SB23 inspection carried out					
Workpack No	CN Inspection Date Inspectors Signature/No.					re/No.

19 October 2017 Amendment 4 Page 6-7



Section 6 : Maintenance Schedule

E 10	MAINTENANC
3	MANUAL

6.5.8 Basket

Basket Type:		
Part No.:	Serial No.:	

Component	Check / Inspect / Record	Pass/Fail (√)/(x)
Basket wires	Inspect for damage	
Basket Frames	Inspect welds for cracking	
Dasket I failles	Inspect tubes for distortion/deformation	
Weave	Inspect for damage, deterioration, completeness	
Rawhide	Inspect for damage, deterioration, completeness	
Floor	Inspect for damage	
Runners	Inspect for damage, wear, security of attachment	
Rope Handles	Inspect for damage security of attachment	
Cylinder Straps	Inspect for damage, deterioration, correct specification, No. of Straps ()	
Pilot Restraint Anchor	Inspect for damage, wear, security of attachment	
Support Rods	Inspect for damage, wear, cracking	
Trim	Inspect for damage, deterioration, completeness	

6.5.8.1 Basket Ancillary Equipment

Component	Check / Inspect / Record	Pass/Fail (√)/(x)
Fire Extinguisher	Check Type, maintained in accordance with manufacturers instructions	
Launch Restraint	Inspect for damage, deterioration, security of fittings, correct operation	
Pilot Restraints	Inspect for damage, deterioration, security of fittings, correct operation	
Instruments	Functional Check (if fitted)	

Workpack No.	CN	Inspection Date	Inspectors Signature/No.

Page 6-8 Amendment 3 21 December 2011



Section 6 : Maintenance Schedule



6.5.9 Fuel Cylinders

No.	Man./Part no.	Serial No.	Initial Test date (Manufacture Date)	Current Test Date	PRV Date
1					
2					
3					
4					
5					
6					

Component	Check / Inspect / Record		Pass/Fail (√)/(x)				
	·			3	4	5	6
Cylinder	Check, Periodic inspection for each cylinder is valid (date)						
Cythidei	Inspect for damage, corrosion						
	Inspect for damage, corrosion, correct operation						
Liquid Valve	Inspect self seal for correct operation, Lubricate/replace as required. SB16/SB17						
	Inspect O-ring seals, Lubricate/replace as required						
Pressure	Check, Date does not exceed life limit, single PRV fitted						
relief valve	Inspect for contamination, corrosion						
Fixed Liquid	Inspect for damage, corrosion, correct operation						
Level Gauge	Inspect Fuelsafe for correct operation/leakage (if fitted)						
Contents Gauge	Inspect for damage, corrosion, freedom of movement						
Vapour Valve	Inspect for damage, corrosion, correct operation (including regulator)						
vapour vatve	Inspect Quick Release Coupling for correct operation, sealing						
Padded Cover	Inspect for damage						
Assembly	Inspect, Leak test all pressure holding joints using leak detector						
Assembly	Functional Test						

Workpack No.	CN	Inspection Date	Inspectors Signature/No.

21 December 2011 Amendment 3 Page 6-9



Section 6: Maintenance Schedule

6.5.10 Other Manufacturers Component Data

For details of the correct continued airworthiness data to be used refer to the Maintenance Programme (Refer to Section 6.5)

Append any additional completed inspection data to this report referencing the Workpack Number.

Number.			
6.5.10.1 Basket			
Manufacturer:			
Type / Part No.:			
Serial No.:			
SB/AD:			
Inspection complete:			
Notes:			
6.5.10.2 Burner			
Manufacturer:			
Type / Part No.:			
Serial No.:			
SB/AD:			
Inspection complete:			
Notes:			
6.5.10.3 Cylinders			
Manufacturer(s):			
Type / Part No.(s):			
Serial No.(s):			
SB/AD:			
Inspection complete:			
Notes:			
Workpack No. CN	Inspec	tion Date	Inspectors Signature/No.

Page 6-10 Amendment 4 19 October 2017